

# Barnacle Remover

## Boatcare

Remover of Shell Fouling



### PRODUCT DESCRIPTION

Barnacle Remover makes it easy to remove barnacles on outdrives, bottoms of boats, or on buoys

- \* Spray application
- \* Shell fouling easily scraped and rinsed off
- \* Does not damage nearby surfaces
- \* Removes minor corrosion on aluminium and bronze

### PRODUCT INFORMATION

Colour	YMB892
Specific Gravity	1.06
Volume Solids	22%
VOC (As Supplied)	0 g/l
Unit Size	500 ml

### DRYING/OVERCOATING INFORMATION

#### Drying

#### Overcoating

##### Substrate Temperature

Overcoated By	5°C (41°F)		10°C (50°F)		23°C (73°F)		35°C (95°F)	
	Min	Max	Min	Max	Min	Max	Min	Max

### APPLICATION AND USE

<b>Preparation</b>	To achieve the best results, scrape off the bulk of the shell fouling before application of Barnacle Remover, leaving the bottom area.
<b>Method</b>	Spray Barnacle Remover over the remaining shells and leave for a couple of minutes. Remove shell fouling by high pressure washing and/or gently scraping. Repeat if necessary. Rinse with fresh water.
<b>Hints</b>	<b>Mixing</b> Shake well before use.
<b>Some Important Points</b>	The product contains hydrochloric acid. Read the label safety section for Health and Safety Information. Remove the spray gun and rinse with water directly after use. Ensure the bottle is closed using the original cap. Product temperature should be minimum 5°C/41°F and maximum 35°C/95°F. Ambient temperature should be minimum 5°C/41°F and maximum 35°C/95°F. Substrate temperature should be minimum 5°C/41°F and maximum 35°C/95°F.
<b>Compatibility/Substrates</b>	Suitable for all substrates and filled surfaces.
<b>Application Methods</b>	Spray

### TRANSPORTATION, STORAGE AND SAFETY INFORMATION

<b>Storage</b>	<b>GENERAL INFORMATION:</b> Exposure to air and extremes of temperature should be avoided. For the full shelf life of Barnacle Remover to be realised ensure that between use the container is firmly closed and the temperature is between 5°C/41°F and 35°C/95°F. Keep out of direct sunlight. <b>TRANSPORTATION:</b> Barnacle Remover should be kept in securely closed containers during transport and storage.
<b>Safety</b>	<b>GENERAL:</b> Barnacle Remover contains chlorhydric acid. Wear suitable respiratory protective equipment. (Combined filter, gas filter B and dust filter P3.) Always use gloves and goggles and keep skin protected with overalls. Read the label safety section for Health and Safety Information, also available from our Technical Help Line. <b>DISPOSAL:</b> Do not discard tins or pour paint into water courses, use the facilities provided. It is best to allow paints to harden before disposal. Remainders of Barnacle Remover cannot be disposed of through the municipal waste route or dumped without permit. Disposal of remainders must be arranged for in consultation with the authorities.

### IMPORTANT NOTES

*The information given in this sheet is not intended to be exhaustive. Any person using the product without first making further written enquiries as to the suitability of the product for the intended purpose does so at their own risk and we can accept no responsibility for the performance of the product or for any loss or damage (other than death or personal*

Please refer to your local representative or visit <http://www.yachtpaint.com> for further information.

All trademarks mentioned in this publication are owned by, or licensed to, the AkzoNobel group of companies. © AkzoNobel 2014.

# Barnacle Remover

## Boatcare

Remover of Shell Fouling



---

*injury resulting from negligence) arising out of such use. The information contained in this sheet is liable to modification from time to time in the light of experience and our policy of continuous product development.*

---

Please refer to your local representative or visit <http://www.yachtpaint.com> for further information.

All trademarks mentioned in this publication are owned by, or licensed to, the AkzoNobel group of companies. © AkzoNobel 2014.

Ref:3289 Barnacle Remover Issue Date:15/12/2014