

**PRODUCT DESCRIPTION**

Advanced wax polish with a fluoro microadditive containing wax. For paintwork and GRP, providing a high gloss finish. Excellent protection against a marine environment. For both manual and machine polishing (800-1000rpm).

- \* Quick and easy to use.
- \* Produces a high gloss, dirt-repellant finish.
- \* Easy to clean surface due to fluoro microadditive content.
- \* Does not discolour scratches.
- \* Also suitable for use on the car, caravan or garden furniture.

**PRODUCT INFORMATION**

<b>Colour</b>	YMB836
<b>Specific Gravity</b>	0.99
<b>Volume Solids</b>	19%
<b>Typical Shelf Life</b>	2 yrs
<b>VOC (As Supplied)</b>	143 g/lt
<b>Unit Size</b>	500 ml

**DRYING/OVERCOATING INFORMATION**

**Drying**

**Overcoating**

**Substrate Temperature**

	5°C (41°F)		10°C (50°F)		23°C (73°F)		35°C (95°F)	
Overcoated By	Min	Max	Min	Max	Min	Max	Min	Max

**APPLICATION AND USE**

<b>Preparation</b>	Clean and degrease with Super Cleaner or Boat Shampoo, and fresh water. Remove discolouration and heavy dirt with Stain Remover if needed. If the surface is in very bad condition you may also need to use Liquid Rubbing.
<b>Method</b>	With a clean, dry cloth or application pad, apply a thin layer to a small area in a small circular motion. Buff off with a clean cloth, or a polishing machine (800-1000 RPM). Seal the surface with UV Wax Sealer.
<b>Hints</b>	<b>Mixing</b> Shake well before use.
<b>Some Important Points</b>	Product temperature should be minimum 5°C/41°F and maximum 30°C/86°F. Ambient temperature should be minimum 5°C/41°F and maximum 30°C/86°F. Substrate temperature should be minimum 5°C/41°F and maximum 30°C/86°F.

**TRANSPORTATION, STORAGE AND SAFETY INFORMATION**

<b>Storage</b>	<b>GENERAL INFORMATION:</b> Exposure to air and extremes of temperature should be avoided. For the full shelf life of UV Polish to be realised ensure that between use the container is firmly closed and the temperature is between 5°C/41°F and 35°C/95°F. Keep out of direct sunlight. <b>TRANSPORTATION:</b> UV Polish should be kept in securely closed containers during transport and storage.
<b>Safety</b>	<b>GENERAL:</b> Read the label safety section for Health and Safety Information, also available from our Technical Help Line. <b>DISPOSAL:</b> Do not discard tins or pour paint into water courses, use the facilities provided. It is best to allow paints to harden before disposal. Remainders of UV Polish cannot be disposed of through the municipal waste route or dumped without permit. Disposal of remainders must be arranged for in consultation with the authorities.

**IMPORTANT NOTES**

*The information given in this sheet is not intended to be exhaustive. Any person using the product without first making further written enquiries as to the suitability of the product for the intended purpose does so at their own risk and we can accept no responsibility for the performance of the product or for any loss or damage (other than death or personal injury resulting from negligence) arising out of such use. The information contained in this sheet is liable to modification from time to time in the light of experience and our policy of continuous product development.*

Please refer to your local representative or visit <http://www.yachtpaint.com> for further information.

All trademarks mentioned in this publication are owned by, or licensed to, the AkzoNobel group of companies. © AkzoNobel 2014.

